



We call it 'Non-Powered, Powered Access.'

As part of the Eco range the EcoLift still harnesses the same Eco friendly revolutionary 'Patented Stored Power System' as the PecoLift but at 4.2 m offers almost a metre extra in working height.

With no batteries (to charge and look after) and no hydraulic oil, the EcoLift is truly an Eco friendly solution.

Typical applications and uses:

1st & 2nd Fix. Pipe Work, M & E. FM.
Cleaning. Painting. Retail. Point of Sale. FM.



Key Features

- Intuitive to operate - turn handle to elevate
- Patented* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (1.28 x 700 mm)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

PUSH AROUND - Self Powered

Indoor Use

Working Height: 4.2 m

Applications: 1st & 2nd fix.
Pipe Work, M&E. F.M. Cleaning.
Painting. Point of Sale. Retail.

Specifications

WORKING DIMENSIONS

Maximum working height:	4.20 m
Maximum platform height:	2.20 m
Basket dimensions:	850 mm (L) x 644 mm (W)
Working footprint:	1.28 m x 700 mm
Safe working load:	150 kg (1 person + tools)
Maximum manual force:	200N
Maximum gradient for operation:	0 degrees
Maximum wind force:	Internal use only, 0 (zero) mph
Maximum wheel force:	234 kg
Sound pressure level:	Less than 70 Dba

CLOSED DIMENSIONS

Length:	1.28 m
Width:	0.70 m
Height:	1.94 m
Weight:	305 kg

LIFT CYCLES Unlimited

Safety features

- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked

